



[VSCP, Back to VSCP Works Technical Information](#)

VSCP Works configuration file format

```

<?xml version = "1.0" encoding = "UTF-8" ?>

<!-- Version 0.0.1    2007-10-26 -->

<vscpworksconfig>

    <general>
        <width>Client window startup width</width>
        <height>Client window startup height</height>
        <xpos>Client window X startup position</xpos>
        <ypos>Client window Y startup position</ypos>
        <path2tempfiles>Path to folder holding temporary
files</path2tempfiles>
        <path2logfile enable="true|false" level="1">Path including filename
to log file</path2logfile>
    </general>

    <vscpclient>
        <VscpRcvFrameRxTextColour r="value" g="value"
b="value"></VscpRcvFrameRxTextColour>
        <VscpRcvFrameRxBgColour r="value" g="value"
b="value"></VscpRcvFrameRxBgColour>
        <VscpRcvFrameTxTextColour r="value" g="value"
b="value"></VscpRcvFrameTxTextColour>
        <VscpRcvFrameTxBgColour r="value" g="value"
b="value"></VscpRcvFrameTxBgColour>
        <VscpRcvFrameLineColour r="value" g="value"
b="value"></VscpRcvFrameLineColour>
        <VscpRcvFrameFont></VscpRcvFrameFont>
        <!-- Enable/Disable grey background on odd rows -->
        <VscpRcvPyjamasStyle>true|false</VscpRcvPyjamasStyle>
        <!-- Enable/Disable autoscroll when filling grid -->
        <Autoscroll>true|false</Autoscroll>
        <VscpRcvShowField0 enable="true|false"></VscpRcvShowField0>
        <VscpRcvShowField1 enable="true|false"></VscpRcvShowField1>
        <VscpRcvShowField3 enable="true|false"></VscpRcvShowField3>
        <VscpRcvShowField4 enable="true|false"></VscpRcvShowField4>
        <VscpRcvShowField5 enable="true|false"></VscpRcvShowField5>
        <VscpRcvShowField6 enable="true|false"></VscpRcvShowField6>
        <VscpRcvShowField7 enable="true|false"></VscpRcvShowField7>
        <VscpRcvFieldText0>Dir</VscpRcvFieldText0>
        <VscpRcvFieldText1>Time</VscpRcvFieldText1>
        <VscpRcvFieldText2>GUID</VscpRcvFieldText2>
        <VscpRcvFieldText3>Class</VscpRcvFieldText3>

```

```
<VscpRcvFieldText4>Type</VscpRcvFieldText4>
<VscpRcvFieldText5>Head</VscpRcvFieldText5>
<VscpRcvFieldText6>Cnt</VscpRcvFieldText6>
<VscpRcvFieldText7>Data</VscpRcvFieldText7>
<VscpRcvFieldText8>Timestamp</VscpRcvFieldText8>
<VscpRcvFieldText9>Note</VscpRcvFieldText9>
<VscpRcvFieldOrder0>0</VscpRcvFieldOrder0>
<VscpRcvFieldOrder1>1</VscpRcvFieldOrder1>
<VscpRcvFieldOrder2>2</VscpRcvFieldOrder2>
<VscpRcvFieldOrder3>3</VscpRcvFieldOrder3>
<VscpRcvFieldOrder4>4</VscpRcvFieldOrder4>
<VscpRcvFieldOrder5>5</VscpRcvFieldOrder5>
<VscpRcvFieldOrder6>6</VscpRcvFieldOrder6>
<VscpRcvFieldOrder7>7</VscpRcvFieldOrder7>
<VscpRcvFieldOrder8>8</VscpRcvFieldOrder8>
<VscpRcvFieldOrder9>9</VscpRcvFieldOrder9>
<VscpRcvFieldWidth0>30</VscpRcvFieldWidth0>
<VscpRcvFieldWidth1>110</VscpRcvFieldWidth1>
<VscpRcvFieldWidth2>250</VscpRcvFieldWidth2>
<VscpRcvFieldWidth3>70</VscpRcvFieldWidth3>
<VscpRcvFieldWidth4>70</VscpRcvFieldWidth4>
<VscpRcvFieldWidth5>60</VscpRcvFieldWidth5>
<VscpRcvFieldWidth6>60</VscpRcvFieldWidth6>
<VscpRcvFieldWidth7>300</VscpRcvFieldWidth7>
<VscpRcvFieldWidth8>90</VscpRcvFieldWidth8>
<VscpRcvFieldWidth9>200</VscpRcvFieldWidth9>
<VscpTrmitFrameTextColour r="value" g="value"
b="value"></VscpTrmitFrameTextColour>
<VscpTrmitFrameBgColour r="value" g="value"
b="value"></VscpTrmitFrameBgColour>
<VscpTrmitFrameLineColour r="value" g="value"
b="value"></VscpTrmitFrameLineColour>
<VscpTrmitFrameFont></VscpTrmitFrameFont>
<VscpTrmitShowField0 enable="true|false"></VscpTrmitShowField0>
<VscpTrmitShowField1 enable="true|false"></VscpTrmitShowField1>
<VscpTrmitShowField2 enable="true|false"></VscpTrmitShowField2>
<VscpTrmitShowField3 enable="true|false"></VscpTrmitShowField3>
<VscpTrmitFieldText0></VscpTrmitFieldText0>
<VscpTrmitFieldText0></VscpTrmitFieldText0>
<VscpTrmitFieldText1></VscpTrmitFieldText1>
<VscpTrmitFieldText2></VscpTrmitFieldText2>
<VscpTrmitFieldText3></VscpTrmitFieldText3>
<VscpTrmitFieldText4></VscpTrmitFieldText4>
<VscpTrmitFieldOrder0></VscpTrmitFieldOrder0>
<VscpTrmitFieldOrder1></VscpTrmitFieldOrder1>
<VscpTrmitFieldOrder2></VscpTrmitFieldOrder2>
<VscpTrmitFieldOrder3></VscpTrmitFieldOrder3>
<VscpTrmitFieldOrder4></VscpTrmitFieldOrder4>
<VscpTrmitFieldWidth0></VscpTrmitFieldWidth0>
<VscpTrmitFieldWidth1></VscpTrmitFieldWidth1>
```

```
<VscpTrmitFieldWidth2></VscpTrmitFieldWidth2>
<VscpTrmitFieldWidth3></VscpTrmitFieldWidth3>
<VscpTrmitFieldWidth4></VscpTrmitFieldWidth4>

</vscpclient>

<vscpinterface>

  <canaldriver> <!-- One or many -->
    <description>Interface description for listBox</description>
    <path>oath to driver</path>
    <config>configstring</config>
    <flags>driver flags</flags>
  </canaldriver>

  <vscpdaemon> <!-- One or many -->
    <description>Interface description for listBox</description>
    <host></host>
    <port></port>
    <username></username>
    <password></password>
    <filter priority="xxx" class="xxx" type="xxx" GUID="xxx" >This
is the row filter</filter>
    <mask priority="xxx" class="xxx" type="xxx" GUID="xxx" >This is
the row mask</mask>
  </vscpdaemon>

</vscpinterface>

</vscpworksconfig>
```

From:
<http://www.vscp.org/docs/vscpworks/> - **VSCP Works**

Permanent link:
http://www.vscp.org/docs/vscpworks/doku.php?id=vscp_works_configuration_file_format

Last update: **2014/07/17 03:27**

